

SCHEDULED MAINTENANCE LOG

MAINTENANCE

36 Months or 30,000 Miles

- | | |
|--|--|
| <input type="checkbox"/> Replace engine oil and oil filter ¹ | <input type="checkbox"/> Inspect nuts and bolts on chassis ² |
| <input type="checkbox"/> Lubricate front axle shaft bushings (GX 470, LX 470) | <input type="checkbox"/> Lubricate drive shaft, re-torque bolts (GX 470, LX 470) |
| <input type="checkbox"/> Measure brake pad thickness and rotor runout | <input type="checkbox"/> Repack front wheel bearings (LX 470) |
| <input type="checkbox"/> Replace air conditioner filter | <input type="checkbox"/> Replace brake fluid |
| <input type="checkbox"/> Replace differential oil (GX 470, LX 470) ² | <input type="checkbox"/> Replace engine air filter |
| <input type="checkbox"/> Replace rear differential oil (RX 330 AWD) ² | |
| <input type="checkbox"/> Replace transfer case oil (GX 470, LX 470, RX 330 AWD) ² | |
| <input type="checkbox"/> Re-torque axle shaft flange bolts (GX 470) | |
| <input type="checkbox"/> Rotate tires | |
| <input type="checkbox"/> Road-test vehicle | |
| <input type="checkbox"/> Inspect the following: | |
| ___ Active height control system (LX 470) | ___ Fuel tank cap gasket |
| ___ Axle shaft boots | ___ Rack and pinion assembly |
| ___ Ball joints and dust covers | ___ Rear differential oil (RX 330 AWD) |
| ___ Body | ___ Steering linkage and boots |
| ___ Brake lines and hoses | ___ Transfer case oil |
| ___ Differential oil (GX 470, LX 470) | ___ Transmission fluid (RX 330) |
| ___ Engine coolant ³ | ___ Variable gear ratio steering assembly (LX 470) |
| ___ Exhaust pipes and mountings | |
| ___ Fuel lines and connections, fuel tank band and fuel tank vapor vent system hoses | |

Date: _____ Mileage: _____

Notes:

- ¹ Reset the oil replacement reminder ("MAINT REQD") light after replacing engine oil.
- ² Required only if vehicle is operated primarily in desert, on dirt roads or while towing.
- ³ Replace only with Genuine Toyota Super Long-Life Coolant or similar high-quality non-silicate, non-amine, non-borate ethylene-glycol coolant with long-life hybrid organic acid technology (i.e., a combination of low phosphates and organic acids).