



2020 GX 460 Specifications

EXTERIOR DIMENSIONS		
Wheelbase		109.8 in.
Overall Length		192.1 in.
Overall Width		74.2 in.
Overall Height* (unloaded)		74.2 in. 73.8 in. Luxury model
Tread Width	Front	62.4 in.
	Rear	62.4 in.
Ground Clearance		8.1 in.
Approach Angle		21 deg.
Departure Angle		23 deg.
Breakover Angle		21 deg.

*Overall height based on EPA loaded vehicle weight, loading conditions.

INTERIOR DIMENSIONS		
Seating Capacity		7
Headroom	Front	38.0 in.
	Middle (outer)	40.4 in.
	Middle (center)	40.2 in.
	Rear	35.2 in.
Legroom	Front	41.7 in.
	Middle	34.1 in.
	Rear	29.3 in.
Shoulder Room	Front	55.4 in.
	Middle	57.3 in.
	Rear	54.5 in.
Hip Room	Front	56.5 in.
	Middle	55.2 in.
	Rear	43.1 in.
Total Interior Volume		4.6 cubic feet
Max Cargo Volume		64.7 cu. ft.

WEIGHTS AND CAPACITIES	
Curb Weight	GX 460: 5,130 lbs.
	GX 460 Luxury: 5,198 lbs.
GVWR	6,600 lbs.



2020 GX 460 Specifications

Weight Distribution – Front/Rear	52/48
Max Towing Capacity	6,500 lbs.
Fuel Capacity	23.0 gal.

ENGINE	
Type, Materials	V8, cast aluminum block and aluminum heads
Designation	1UR-FE
Valvetrain	DOHC 32 valve with Dual Hydraulic with intelligence (VVT-i)
Displacement	4.6 liter—281.1 cubic inches
Bore x Stroke	3.70 in. x 3.27 in.
Compression Ratio	10.2:1
Horsepower (SAE)	301 hp @ 5,500 rpm
Torque	329 lb.-ft. @ 3,500 rpm
Fuel System	Sequential Multiport Fuel Injection (SFI); Electronic Throttle Control System with intelligence (ETCS-i)
Fuel Requirement	91 octane unleaded
Emission Certification	ULEV-II

DRIVETRAIN															
Layout	Front engine, full-time four-wheel drive (4WD)														
Transmission Type	6-speed sequential shift automatic Electronically Controlled Transmission (ECT)														
Designation	A760F														
Gear Ratios	<table border="0"> <tr> <td>1st</td> <td>3.520</td> </tr> <tr> <td>2nd</td> <td>2.042</td> </tr> <tr> <td>3rd</td> <td>1.400</td> </tr> <tr> <td>4th</td> <td>1.000</td> </tr> <tr> <td>5th</td> <td>0.716</td> </tr> <tr> <td>6th</td> <td>0.586</td> </tr> <tr> <td>Reverse</td> <td>3.224</td> </tr> </table>	1 st	3.520	2 nd	2.042	3 rd	1.400	4 th	1.000	5 th	0.716	6 th	0.586	Reverse	3.224
1 st	3.520														
2 nd	2.042														
3 rd	1.400														
4 th	1.000														
5 th	0.716														
6 th	0.586														
Reverse	3.224														
Differential Gear Ratio	3.909														
Transfer Gear Ratio (Hi/Lo)	1.000/2.566														
Center Differential Type	TORSEN [®] Limited Slip with electronic locking feature														



2020 GX 460 Specifications

CHASSIS AND BODY		
Body/Frame	Steel body mounted on steel perimeter frame	
Suspension	Front	Double wishbone, coil springs, stabilizer bar
	Rear	4-link rigid axle, coil springs, stabilizer bar (GX 460 and GX 460 Premium models); 4-link rigid axle, pneumatic cylinder assembly, stabilizer bar (GX 460 Luxury models) Hydraulic Type
Suspension control system	Kinetic Dynamic Suspension System	
Damping and height controls	GX 460 Luxury model only: Adaptive Variable Suspension (AVS); Adjustable Height Control (AHC)	
Steering Type	Engine speed sensing power-assisted rack and pinion with Variable Gear Ratio Steering (VGRS)	
	Overall Ratio	18.4
	Turn (lock to lock)	3.0
	Turning Circle (wall to wall)	41.4 ft.
Brakes	Type	Ventilated front and rear disc with Anti-lock Braking System (ABS), Multi-Terrain ABS, Brake Assist (BA) and Electronic Brake-force Distribution (EBD)
	Front	13.3 in. vented disc
	Rear	12.3 in. vented disc
Anti-lock Braking System	4-channel, 4-sensor	
Wheel Size/Type	18 x 7.5-inch aluminum alloy	
Tire Size/Type	265/60R18 mud and snow (full size alloy spare)	
Tire Brand (s)	Bridgestone, Michelin	

PERFORMANCE	
0-60 mph Acceleration (mfg. results)	7.8 sec.
0 – ¼ Mile Acceleration	16.6 sec.
Top Track Speed	110 mph – electronically limited
Estimated Fuel Economy* (City/Hwy/Combined)	15/20/17 mpg
Coefficient of Drag (Cd)	0.35

* Actual mileage will vary.