

Group	L"	W"	H"	Lmm	Wmm	Hmm	~Weight	~CCA	
35	9.1	6.9	8.9	230	175	225	36 lb	640-685	
41	11.6	6.9	6.9	293	175	175	32-35 lb	650	
42	9.6	6.8	6.8	243	173	173	27-28 lb	500	
47	9.7	6.9	7.5	246	175	190		600	cross-listed w/ Group 90/T5
48	12.1	6.9	7.6	278	175	190	39-41 lb	690-730	
54	7.3	6.1	8.4	186	154	212			
55	8.6	6.1	8.4	218	154	212	29 lb	500-540	55/56/62 interchangeable??
56	10	6.1	8.4	254	154	212	29-33 lb	550-590	
61	7.6	6.4	8.9	192	162	225			
62	8.9	6.4	8.9	225	162	225	29 lb		
63	10.2	6.4	8.9	258	162	225			
64	11.7	6.4	8.9	296	162	225	41 lb	620	
85	9.1	6.8	8	230	173	203	32 lb	625-650	
90	9.5	6.9	6.9	242	175	175	32 lb	520-650	
91	11	6.9	6.9	278	175	175	42 lb		
22F	9.5	6.9	8.3	240	175	211	30 lb	425-450	
22NF	9.4	5.5	8.9	240	140	227		390	
24F	10.3	6.8	8.9	260	175	225	36-39 lb	700-715	typical replacement
26R	8.2	6.9	7.8	208	175	197	28 lb	525	
<b>27F</b>	<b>12.1</b>	<b>6.8</b>	<b>8.9</b>	<b>306</b>	<b>175</b>	<b>225</b>	<b>44 lb</b>		<b>2JZ: 450 CCA min, 1UZ: 625</b>
34R	10.3	6.8	7.9	260	173	200	35-38 lb	800-825	
40R	10.9	6.9	6.9	278	175	175	38 lb		
48/91	12.1	6.9	7.6	306	175	192			
51R	9.4	5.1	8.8	238	129	223	27-28 lb	400-500	
96R	9.6	6.2	6.9	242	173	175	33 lb	590-600	
97R	9.9	6.9	7.5	252	175	190	38 lb	600	
98R	11.2	6.9	7.5	283	175	190			

www.batteryweb.com/bci.cfm – filtered by polarity/terminals (R/H-POSTOP, SAE AUTO) & max dimensions

\* 6.9" (W) models okay by 175mm spec

\* ignored cheap models for CCA range wherever possible, e.g. looked at Duralast Gold not Duralast