

# 1999 LEXUS **RX** Specifications

ENGINE Type 60° V6, aluminum block and heads

**Displacement** 3.0 liters (183 cubic inches)

**Valvetrain** Four cam, four valves per cylinder, with

continuously Variable Valve Timing

with intelligence (VVT-i)

Compression Ratio 10.5:1

**Horsepower at RPM** 220 hp @ 5,800

Torque at RPM 222 lb-ft @ 4,400

DRIVETRAIN | Type Front-wheel drive (FWD) with optional Traction Conrol

System (TRAC) or full-time all-wheel drive (AWD) with viscous coupling center differential and optional torque-

sensing limited-slip rear differential.

**Transmission** Four-speed automatic Electronically

Controlled Transmission (ECT).

Dual shift programs, engine/
transmission networking, flex-lockup

torque converter, Slope Compensation Control.

Final Drive Ratio 3.08:1 (FWD) / 3.29:1 (AWD)

BODY, DIMENSIONS

**Type** Five-passenger luxury sport-utility

Construction Welded-steel unibody

Overall Length 180.1 in

**Width** 71.5 in

**Height** 65.7 in (unloaded)

Wheelbase 103.1 in Ground Clearance 7.7 in

Approach Angle 28 degrees

**Departure Angle** 23 degrees

Cargo Capacity (max) 39.8 cubic feet (rear seats forward) <sup>1</sup>

75.0 cubic feet (rear seats folded) 1

Curb Weight 3,692 lb (FWD)

3,900 lb (AWD)

Vehicle Capacity Weight 880 lb1

Gross Vehicle Weight Rating 4,950 lb1

Tow Rating (max)  $3,500 lb^2$ 

Fuel-tank Capacity 17.2 gallons

**Headroom** 39.5/39.2 in (front/rear)

38.1/38.6 in (front/rear)

with available moonroof

**Legroom** 40.7/36.4 in (front/rear)

**Shoulder Room** 57.6/56.7 in (front/rear)



71.5'



7.7"

### **CLEXUS** | **KNOWLEDGE** CENTER

#### **CHASSIS**

Suspension Front: Independent, MacPherson struts with coil springs,

L-shaped lower arms, gas-pressurized shock absorbers,

stabilizer bar.

Rear: Independent, MacPherson struts with coil springs, dual links, strut rods, gas-pressurized shock absorbers,

stabilizer bar.

**Steering** Engine-speed-sensing, progressive power-assisted

rack-and-pinion. 2.6 turns, lock to lock.

Brakes Four-wheel power-assisted discs, with four-sensor, four-

channel Anti-lock Braking System (ABS). 11.3-in vented

front discs, 11.7-in solid rear discs.

Wheels 16 x 6.5-in alloy wheels

Original Equipment Tires All-Season Goodyear Integrity P225/70SR16 - 101S

(Code: 402-469-477-OD) or All-Season Bridgestone

Dueler HT687 P225/70SR16 - 101S (Code: 064-378).

Full-size spare with alloy wheel.

# 1999 LEXUS **RX** Specifications (Continued)

#### PERFORMANCE

**0-60 MPH Acceleration** 8.5 seconds (FWD)<sup>3</sup> 8.8 seconds (AWD)<sup>3</sup>

1/4-Mile Acceleration  $16.4 \text{ seconds (FWD)}^3$ 

16.6 seconds (AWD)<sup>3</sup>

**Top Track Speed** 112 mph (electronically limited)<sup>3</sup>

Estimated Fuel Consumption 19/24 mpg (FWD)<sup>4</sup> (estimated city/highway) 19/22 mpg (AWD)<sup>4</sup>

Aerodynamic Drag Coefficient 0.36

Turning Circle (curb-to-curb) 41.3 ft.

## TOTAL UNITS PRODUCED

Front-wheel drive 21,978 All-wheel drive 68,360

**Total** 90,338

### **DISCLAIMERS**

- <sup>1</sup> Cargo and load capacity limited by weight and distribution.
- <sup>2</sup> Before towing, confirm your vehicle and trailer are compatible, hooked up properly and you have all necessary additional equipment. Do not exceed any Weight Ratings and review all instructions and cautions from your trailer hitch manufacturer and Lexus vehicle *Owner's Manual*. Note that the maximum amount you can tow depends on the total weight of any cargo, occupants and available equipment in the vehicle.
- <sup>3</sup> Performance capacity figures are for comparison only and were obtained with prototype vehicles by professional drivers using special safety equipment and procedures. Do not attempt.
- <sup>4</sup> Actual mileage will vary with options, driving conditions, driving habits and vehicle's condition. Results reported to EPA indicate that the majority of vehicles with these estimates will achieve between 16 and 22 mpg in the city and between 20 and 28 mpg on the highway (FWD RX), and between 16 and 22 mpg in the city and between 18 and 26 mpg on the highway (AWD RX) (See www.fueleconomy.gov.).



# 1999 LEXUS **RX** Original Pricing and Options

#### PRICING

 <u>Code</u>	<u>Description</u>	Manufacturer's Suggested Retail Price (MSRP) <sup>5</sup>
9400	RX 300 FWD Luxury Sport Utility	\$ 32,045
9410	RX 300 FWD Luxury Sport Utility, equipped with CA/NY Emissions	32,045
9404	RX 300 AWD Luxury Sport Utility	33,445
9414	RX 300 AWD Luxury Sport Utility, equipped with CA/NY Emissions	33,445
	Options	
DC	In-Dash 6-CD Auto-Changer	1,050
HH	Two-Level Heated Front Seats , requires PM	420
LA	Leather Trim Package	1,240
LD	RX 300 AWD: Torsen® Rear Limited Slip Differential (LSD)	375
NK	Lexus/Nakamichi® Premium Audio with In-Dash 6-CD Auto-Changer	1,600
PM	Premium Package, includes Leather Trim Package, Driver's Seat Memory, Electrochromic Inside and Outside Mirrors, Programmable Garage Door Opener, and Interior Air Filter	1,860
PZ	Limited Package, includes Leather Trim Package, Driver's Seat Memory, Programmable Garage Door Opener, and Interior Air Filter, requires LA	1,760
SR	Power Moonroof	1,000
TN	RX 300 FWD: Traction Control System (TRAC)	300

<sup>&</sup>lt;sup>5</sup>The vehicle MSRP at launch included Delivery, Processing, and Handling fee. The Delivery, Processing, and Handling Fee was based on the value of the processing, handling and delivery services provided by Lexus and Lexus' overall pricing strategy. Federal, state, and local taxes, and advertising fees, if any, were additional. Prices included predelivery services. Suggested prices: These guidelines were provided by Lexus. The dealer was free to establish its own selling price, margin, or profit level.



#### **EXTERIOR COLORS**





