

SCHEDULED MAINTENANCE LOG

36 Months or 30,000 Miles

- | | |
|---|--|
| <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Replace engine oil with 0W-20 oil; replace oil filter <input checked="" type="checkbox"/> Reset maintenance reminder light <input checked="" type="checkbox"/> Rotate tires <input checked="" type="checkbox"/> Re-torque nuts and bolts of drive shaft (RX 350 AWD) <input checked="" type="checkbox"/> Replace air conditioner filter <input checked="" type="checkbox"/> Replace brake fluid <input checked="" type="checkbox"/> Replace engine air filter <input checked="" type="checkbox"/> Inspect the following: <ul style="list-style-type: none"> <input type="checkbox"/> Axle shaft boots <input type="checkbox"/> Ball joints and dust covers <input type="checkbox"/> Body <input type="checkbox"/> Brake lines and hoses <input type="checkbox"/> Brake rotor thickness and runout <input type="checkbox"/> Engine coolant (RX 350; see page 28) <input type="checkbox"/> Engine/inverter coolant (RX 450h; see page 28) <input type="checkbox"/> Exhaust pipes and mountings <input type="checkbox"/> Fuel lines and connections, fuel tank band and fuel tank vapor vent system hoses | <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Replace Smart Key battery <input checked="" type="checkbox"/> Tighten axle shaft bolts (RX 450h AWD) <input checked="" type="checkbox"/> Visually inspect brake pads, calipers and rotors <input checked="" type="checkbox"/> Check installation of driver's floor mat <input checked="" type="checkbox"/> Road-test vehicle <input type="checkbox"/> Fuel tank cap gasket <input type="checkbox"/> Rack and pinion assembly <input type="checkbox"/> Rear differential oil (AWD only) <input type="checkbox"/> Steering linkage and boots <input type="checkbox"/> Transfer case oil (RX 350 AWD) <input type="checkbox"/> Transmission fluid <input type="checkbox"/> Variable gear ratio steering assembly (RX 450h) |
|---|--|

If you drive primarily under either of these special operating conditions, perform these additional items:

Driving off-road, on dirt roads or on dusty roads:

- Tighten nuts and bolts on chassis

Towing a trailer, using a car-top carrier or heavy vehicle loading:

- Replace rear differential oil (RX 350 AWD)
- Replace transfer case oil (RX 350 AWD)
- Tighten nuts and bolts on chassis



Date: Nov 14-11 Mileage: 3006